



Unit shown with service panels removed. Representative drawing only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4" for bottom opening.



For complete warranty details visit [www.AspenMfg.com](http://www.AspenMfg.com)

### Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed
- Left- or right-hand refrigerant and plumbing connections
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2 3 ton and 7/8" ODS on 3-1/2 - 5 ton
- Externally mounted flowrater body with Schrader valve for hiss-testing
- Heavy duty plastic drain pans on most models
- Embossed galvanized cabinets standard. Cabinets feature furnace connectors (patent pending)
- Upflow without field modification. Downflow applications require plate kit, not included
- Split access doors in front for easy service
- Fully insulated cabinets with faced insulation
- Ten-year limited warranty
- AHRI certifiable with all brands of A/C and heat pump systems
- ETL listed for use with R-22 and R410A when proper metering device is used

### CUSTOMIZATION

- Factory or field-installable TXV available
- Painted cabinets
- Powder-painted metal or stainless pans
- Schrader mounted on suction manifold, external to cabinet
- Bikini cabinets

COIL MODEL	NOMINAL CAPACITY (BTUs)	PISTON SIZE		DIMENSIONS			SHIPPING INFORMATION			
		R-22	R 410-A	CABINET WIDTH (W")	CABINET DEPTH (D")	MAX FURNACE WIDTH (OR HEIGHT WHEN HORIZONTAL)	SHIPPING WEIGHT (LBS)			SKID QTY
							2 ROW	3 ROW	4 ROW	
CC24A*	24,000	0.059	14	23	21-1/2	16	29	37	45	20
CC24B*		0.059	14	23	21-1/2	16	34	44	52	20
CC24C*		0.059	14	23	21-1/2	20	39	50	59	16
CC24D*		0.059	14	23	21-1/2	20	44	56	67	16
CC30A*	30,000	0.068	14	23	21-1/2	16	34	44	52	20
CC30B*		0.068	14	23	21-1/2	20	39	50	59	16
CC30C*		0.068	14	23	21-1/2	20	44	56	67	16
CC30D*		0.068	14	23	21-1/2	24	49	62	74	12
CC30E*		0.068	14	23	21-1/2	24	51	64	76	12
CC36A*	36,000	0.074	2/3R - 14, 4R - 17	23	21-1/2	20	39	50	59	16
CC36B*		0.074	2/3R - 14, 4R - 17	23	21-1/2	20	44	56	67	16
CC36C*		0.074	2/3R - 14, 4R - 17	23	21-1/2	24	49	62	74	12
CC36D*		0.074	2/3R - 14, 4R - 17	23	21-1/2	24	54	69	82	12
CC36E*		0.074	2/3R - 14, 4R - 17	23	21-1/2	20	39	50	59	16
CC36F*		0.074	17	26-1/2	21-1/2	28	63	81	96	12
CC42A*	42,000	0.080	17	26-1/2	21-1/2	20	44	56	67	16
CC42B*		0.080	17	26-1/2	21-1/2	24	49	62	74	12
CC42C*		0.080	17	26-1/2	21-1/2	24	54	69	82	12
CC42D*		0.080	17	26-1/2	21-1/2	28	58	75	89	12
CC42E*		0.080	17	26-1/2	21-1/2	20	44	45	67	16
CC42F*		0.080	17	26-1/2	21-1/2	28	63	81	96	12
CC48A*	48,000	0.084	17	26-1/2	21-1/2	24	49	62	74	12
CC48B*		0.084	17	26-1/2	21-1/2	24	54	69	82	12
CC48C*		0.084	17	26-1/2	21-1/2	28	58	75	89	12
CC48D*		0.084	17	26-1/2	21-1/2	28	63	81	96	12
CC48E*		0.084	17	26-1/2	21-1/2	28	60	77	91	12
CC48G*		0.084	17	26-1/2	21-1/2	28	65	83	98	12
CC60A*	60,000	0.092	20-1/2	26-1/2	21-1/2	28	58	75	89	12
CC60B*		0.092	20-1/2	26-1/2	21-1/2	28	63	81	96	12
CC60C* (3)		0.092	20-1/2	26-1/2	23	28	66	84	100	12
CC60D* (3)		0.092	20-1/2	26-1/2	23	28	71	91	108	12
CC60E* (3)		0.092	24-1/2	26-1/2	21-1/2	28	79	101	120	12
CC60F*		0.092	20-1/2	26-1/2	21-1/2	28	60	77	91	12
CC60G* (4)		0.092	24-1/2	26-1/2	21-1/2	28	81	103	122	12

Notes: 1) Not all drain pan sizes are currently available in heavy duty plastic. Check with your local Aspen representative for current availability. 2) Do not use heavy duty plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290°F +/-5°F. Specify metal drain pans for these applications. 3) Metal drain pan. Slab is rotated 90° inside cabinet. Refrigerant and plumbing connections still exit cabinet front. 4) Metal drain pan.

Revised 2/24.

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. ©2024